## C Series Clamp-On Chainwheels

'C' Series chainwheels are highly robust and ideal for the heaviest of industrial applications and corrosive environments. Perfect for valves that need to withstand especially heavy use.

- Ductile iron clamp-on chain sprocket fits hand wheel sizes from 152 to 1,016 mm (6 to 40") in diameter
- Clamps onto existing handwheel for safe and effective manual valve operation
- All units come complete with sprocket wheel, chain guide, set collar, zinc plated hardware and installation instructions
- Available in galvanised option







C-Series – Clamp-On Chainwheel						
Model No.	For Use With Valve Handwheel Diameter in (mm)	Domestic/ Metric Weight Ibs (kg)	Chain & Roto Link Size	Additional Chain Needed for Loop ft. (mm)	Chain Weight Per ft. Ibs (kg)	RCK Safety Kit Size
C9	6 - 9 <sup>3</sup> / <sub>4</sub> (152 - 248)	16 (7.26)	1/0	2 (610)	0.17 (0.08)	RCK <sup>3</sup> / <sub>16</sub>
C12	10 - 12 <sup>3</sup> / <sub>4</sub> (254 - 324)	22 (9.98)	1/0	3 (914)	0.17 (0.08)	RCK <sup>3</sup> / <sub>16</sub>
C15	13 - 16 (330 - 406)	37 (16.78)	4/0	4 (1,219)	0.31 (0.14)	RCK <sup>1</sup> / <sub>4</sub>
C18	16 <sup>1</sup> / <sub>2</sub> - 19 (419 - 483)	44 (19.96)	4/0	4 (1,219)	0.31 (0.14)	RCK <sup>1</sup> / <sub>4</sub>
C30	26-32 (660-813)	98 (44.45)	5/0	8 (2,438)	0.35 (0.16)	RCK <sup>5</sup> / <sub>16</sub>
C40	32 - 40 (813 - 1,016)	146 (66.22)	5/0	11 (3,353)	0.35 (0.16)	RCK <sup>5</sup> / <sub>16</sub>