

## E Series Direct Mount Chainwheels

Custom fit chainwheels that mount directly on to the valve stem and replace the hand wheel. The fitting of the chainwheel to the valve is streamlined and secure and the need for multiple clamps and hardware sets is eliminated. Available in lightweight aluminium and ductile iron.

- All units come complete with sprocket wheel, chain guide, set collar and installation instructions
- The aluminium version replaces handwheel sizes from 102 to 768 mm (4 to 30 1/4")
- The ductile iron version replaces handwheel sizes from 216 to 768 mm (8 1/2 to 30 1/4")
- Available in galvanised option



E-Series – Direct Mount Chainwheel							
Model No.	Hand Wheel Diameter in (mm)	Weight		Chain & Roto Link Size	Additional Chain Needed for Loop ft. (mm)	Chain Weight Per ft. lbs (kg)	RCK Safety Kit Size
		Ductile iron lbs (kg)	Alum. lbs (kg)				
E6	6 3/16 (157)	N/A	3 (1.36)	#2	1 (305)	0.10 (0.05)	RCK 3/16
E9	8 9/16 (218)	14 (6.35)	7 (3.18)	1/0	2 (610)	0.17 (0.08)	RCK 3/16
E12	12 3/4 (324)	26 (11.79)	12 (5.44)	1/0	3 (914)	0.17 (0.08)	RCK 3/16
E15	15 (381)	46 (20.87)	22 (9.98)	4/0	4 (1,219)	0.31 (0.14)	RCK 1/4
E18	18 1/4 (464)	69 (31.30)	31 (14.06)	4/0	4 (1,219)	0.31 (0.14)	RCK 1/4
E24	24 1/4 (616)	107 (48.53)	50 (22.68)	5/0	6 (1,829)	0.35 (0.16)	RCK 5/16
E30	30 1/4 (768)	149 (67.59)	69 (31.30)	5/0	8 (2,438)	0.35 (0.16)	RCK 5/16