

M Series Clamp On and Direct Mount

The M Series hammer blow actuator mimics the motion of a hammer striking an anvil, delivering a measured blow to free sticky and/or damaged valves.

- Available in chain model for above ground level operation or handwheel model for ground level operation
- Both styles available in clamp-on or direct-mount installation (direct-mount furnished with adapter plate, replacing existing handwheel)
- Available in galvanised option



M-Series – Hammer Blow Clamp-On						
Model No.	Valve Hand Wheel Diameter in (mm)	Weight lbs (kg)	Chain Size	Additional Chain Needed for Loop ft. (mm)	Chain Weight Per ft. lbs (kg)	RCK Safety Kit Size
M9	7 - 9 ³ / ₄ (178 - 248)	25 (11.34)	1/0	2 (610)	0.17 (0.08)	RCK ³ / ₁₆
M12	10 - 12 ³ / ₄ (254 - 324)	51 (23.13)	1/0	3 (914)	0.17 (0.08)	RCK ³ / ₁₆
M15	13 - 16 ³ / ₄ (330 - 425)	67 (30.39)	4/0	4 (1,219)	0.31 (0.14)	RCK ¹ / ₄
M18	17 - 19 ¹ / ₂ (432 - 495)	89 (40.37)	4/0	4 (1,219)	0.31 (0.14)	RCK ¹ / ₄
M24	20 - 25 (508 - 635)	138 (62.60)	5/0	6 (1,829)	0.35 (0.16)	RCK ⁵ / ₁₆

M-Series – Hammer Blow Direct-Mount						
Model No.	Valve Hand Wheel Diameter in (mm)	Weight lbs (kg)	Chain Size	Additional Chain Needed for Loop ft. (mm)	Chain Weight Per ft. lbs (kg)	RCK Safety Kit Size
M9	7 - 9 ³ / ₄ (178 - 248)	29 (13.15)	1/0	2 (610)	0.17 (0.08)	RCK ³ / ₁₆
M12	10 - 12 ³ / ₄ (254 - 324)	56 (25.40)	1/0	3 (914)	0.17 (0.08)	RCK ³ / ₁₆
M15	13 - 16 ³ / ₄ (330 - 425)	78 (35.38)	4/0	4 (1,219)	0.31 (0.14)	RCK ¹ / ₄
M18	17 - 19 ¹ / ₂ (432 - 495)	123 (55.79)	4/0	4 (1,219)	0.31 (0.14)	RCK ¹ / ₄
M24	20 - 28 (508 - 711)	168 (76.20)	5/0	6 (1,829)	0.35 (0.16)	RCK ⁵ / ₁₆
M30	30 (762) or larger	215 (97.52)	5/0	8 (2,438)	0.35 (0.16)	RCK ⁵ / ₁₆